

Product Information

02 05 180

High Leverage Combination Pliers



- 35% less effort required than with conventional combination pliers
- With cutting edges (hardness approx. 63 HRC) for heavy duty
- Easier work due to optimised leverage
- Easier cutting, powerful gripping, bending and pulling
- Long cutting edges for thicker cables
- With gripping zones for flat and round material, suitable for versatile use
- Precise, minimal light gap between the gripping jaws to ensure optimal function of the cutting edges
- Cutting edges additionally induction-hardened, cutting edge hardness approx.
 63 HRC
- With comfort handles: consisting of three ergonomic components for optimized handling and equipped with two KNIPEXtend interfaces for extensions



General		
Article No.	02 05 180	
EAN	4003773043072	
pliers	chrome-plated	
head	chrome-plated	
handles	with comfort handles	
Weight	236 g	
Dimensions	184 x 51 x 21 mm	
Standard	DIN ISO 5746	
REACH compliant	does not contain SVHC	
RoHS compliant	not applicable	
Technical details		
Cutting capacities hard wire (diameter)	Ø 2.5 mm	
Cutting capacities piano wire (diameter)	Ø 2.0 mm	
Cutting capacity copper cable, multiple-stranded	Ø 11.5 mm	
Cutting capacity copper cable, multiple-stranded	16.0 mm ²	

Technical changes and errors excepted

KNIPEX Quality – Made in Germany









Product Information

02 05 200

High Leverage Combination Pliers



- 35% less effort required than with conventional combination pliers
- With cutting edges (hardness approx. 63 HRC) for heavy duty
- Easier work due to optimised leverage
- Easier cutting, powerful gripping, bending and pulling
- Long cutting edges for thicker cables
- With gripping zones for flat and round material, suitable for versatile use
- Precise, minimal light gap between the gripping jaws to ensure optimal function of the cutting edges
- Cutting edges additionally induction-hardened, cutting edge hardness approx.
 63 HRC
- With comfort handles: consisting of three ergonomic components for optimized handling and equipped with two KNIPEXtend interfaces for extensions



General		
Article No.	02 05 200	
EAN	4003773043089	
pliers	chrome-plated	
head	chrome-plated	
handles	with comfort handles	
Weight	342 g	
Dimensions	200 x 56 x 20 mm	
Standard	DIN ISO 5746	
REACH compliant	does not contain SVHC	
RoHS compliant	not applicable	
Technical details		
Cutting capacities hard wire (diameter)	Ø 2.8 mm	
Cutting capacities piano wire (diameter)	Ø 2.2 mm	
Cutting capacity copper cable, multiple-stranded	Ø 13.0 mm	
Cutting capacity copper cable, multiple-stranded	25.0 mm²	

Technical changes and errors excepted


KNIPEX Quality – Made in Germany















Product Information

02 05 225

High Leverage Combination Pliers



- 35% less effort required than with conventional combination pliers
- With cutting edges (hardness approx. 63 HRC) for heavy duty
- Easier work due to optimised leverage
- Easier cutting, powerful gripping, bending and pulling
 Long cutting edges for thicker cables
- With gripping zones for flat and round material, suitable for versatile use
- Precise, minimal light gap between the gripping jaws to ensure optimal function of the cutting edges
- Cutting edges additionally induction-hardened, cutting edge hardness approx.



General		
Article No.	02 05 225	
EAN	4003773010005	
pliers	chrome-plated	
head	chrome-plated	
handles	with comfort handles	
Weight	410 g	
Dimensions	225 x 53 x 24 mm	
Standard	DIN ISO 5746	
REACH compliant	does not contain SVHC	
RoHS compliant	not applicable	
Technical details		
Cutting capacities hard wire (diameter)	Ø 3.0 mm	
Cutting capacities piano wire (diameter)	Ø 2.5 mm	
Cutting capacity copper cable, multiple-stranded	Ø 14.0 mm	
Cutting capacity copper cable, multiple-stranded	25.0 mm ²	

Technical changes and errors excepted

KNIPEX Quality – Made in Germany











