

03 07 160

Combination Pliers



- With gripping zones for flat and round material, suitable for versatile use
- With cutting edges for soft and hard wire
- Long cutting edges for thicker cables
- Cutting edges additionally induction-hardened, cutting edge hardness approx.
 60 HRC

≜ 1000¥	24	
E IOOO I		ALC: U

General	
Article No.	03 07 160
EAN	4003773015307
pliers	chrome-plated
head	chrome-plated
handles	with dipped insulation, VDE-tested
Weight	254 g
Dimensions	160 x 67 x 32 mm
Standard	DIN ISO 5746 DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Cutting capacities medium hard wire (diameter)	Ø 3.1 mm
Cutting capacities hard wire (diameter)	Ø 2.0 mm
Cutting capacity copper cable, multiple-stranded	Ø 10.0 mm
Cutting capacity copper cable, multiple-stranded	16.0 mm ²
VDE tested	yes

Technical changes and errors excepted









03 07 180

Combination Pliers



- With gripping zones for flat and round material, suitable for versatile use
- With cutting edges for soft and hard wire
- Long cutting edges for thicker cables
- Cutting edges additionally induction-hardened, cutting edge hardness approx.
 60 HRC



General	
Article No.	03 07 180
EAN	4003773015314
pliers	chrome-plated
head	chrome-plated
handles	with dipped insulation, VDE-tested
Weight	285 g
Dimensions	180 x 65 x 31 mm
Standard	DIN ISO 5746 DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Cutting capacities medium hard wire (diameter)	Ø 3.4 mm
Cutting capacities hard wire (diameter)	Ø 2.2 mm
Cutting capacity copper cable, multiple-stranded	Ø 12.0 mm
Cutting capacity copper cable, multiple-stranded	16.0 mm²

yes

Technical changes and errors excepted

VDE tested










03 07 200

Combination Pliers



- With cutting edges for soft and hard wire Long cutting edges for thicker cables
- Cutting edges additionally induction-hardened, cutting edge hardness approx. $60\ \mathrm{HRC}$





5321 ted
ted
tad
ncu
d insulation, VDE-tested
31 mm
46 DIN EN 60900 IEC 60900
ontain SVHC
ontain 64116

Technical details	
Cutting capacities medium hard wire (diameter)	Ø 3.8 mm
Cutting capacities hard wire (diameter)	Ø 2.5 mm
Cutting capacity copper cable, multiple-stranded	Ø 13.0 mm
Cutting capacity copper cable, multiple-stranded	16.0 mm²
VDE tested	yes

Technical changes and errors excepted









03 07 250

Combination Pliers

- With gripping zones for flat and round material, suitable for versatile use
- With cutting edges for soft and hard wire Long cutting edges for thicker cables
- Cutting edges additionally induction-hardened, cutting edge hardness approx. $60\ \mathrm{HRC}$





General	
Article No.	03 07 250
EAN	4003773015345
pliers	chrome-plated
head	chrome-plated
handles	with dipped insulation, VDE-tested
Weight	597 g
Dimensions	250 x 73 x 36 mm
Standard	DIN ISO 5746 DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Cutting capacities medium hard wire (diameter)	Ø 3.8 mm

Technical details	
Cutting capacities medium hard wire (diameter)	Ø 3.8 mm
Cutting capacities hard wire (diameter)	Ø 2.5 mm
Cutting capacity copper cable, multiple-stranded	Ø 15.0 mm
Cutting capacity copper cable, multiple-stranded	25.0 mm²
VDE tested	yes

Technical changes and errors excepted





