

Micrometer

Disc Micrometers SERIES 223, 123

- Can be used for making root tangent measurements on spur gears and helical gears.
- Determination of the root tangent length: refer to "Quick Guide to Precision Measuring Instruments" on page 13-8.
- Equipped with Ratchet Stop for constant measuring force.



123-101

SPECIFICATIONS

Metric							
Code No.	Range (mm)	Graduation (mm)	Maximum permissible error J_{MPE} (μm)	Flatness (μm)	Parallelism (μm)	Anvil dia. (mm)	Measurable module
Mechanical counter model							
223-101	0 - 25	0.01	± 4	1	4	$\varnothing 20$	0.5 - 6
223-102	25 - 50						
Analog							
123-101	0 - 25	0.01	± 4	1	4	$\varnothing 20$	0.5 - 6
123-113*							
123-102	25 - 50						
123-114*							
123-103					50 - 75		
123-115*							
123-104	75 - 100		± 6	6			
123-116*							
123-105	100 - 125		± 7	1.6	7	$\varnothing 30$	0.7 - 11
123-106	125 - 150						
123-107	150 - 175						
123-108	175 - 200						
123-109	200 - 225						
123-110	225 - 250						
123-111	250 - 275	± 8	9				
123-112	275 - 300						
Inch							
Code No.	Range (in)	Graduation (in)	Maximum permissible error J_{MPE} (in)	Flatness (in)	Parallelism (in)	Anvil dia. (in)	Measurable module
Mechanical counter model							
223-125	0 - 1	0.001	± 0.0002	0.00004	0.0002	$\varnothing 0.787$	0.5 - 6
Analog							
123-125	0 - 1	0.001	± 0.0002	0.00004	0.0002	$\varnothing 0.787$	0.5 - 6
123-126	1 - 2						
123-127	2 - 3		± 0.0003		0.0003		
123-128	3 - 4						

* The measuring discs have carbide tips.

• Standard accessories: Setting standard, 1 pc. (except for measuring range 0 to 25 mm (0 to 1 in) models), Spanner (301336), 1 pc.
Note: Root tangent length measurement is not available for some types of gears.



Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của NPOWER
Bản quyền nội dung thuộc về Mitutoyo

Powered by NAVITECH | www.navitech.co
www.npower.com.vn

Disc Micrometers
SERIES 223, 123

DIMENSIONS

Analog models up to 50 mm measuring range Unit: mm

Analog models over 50 mm measuring range

Range (mm)	L	a	b	c	e	f	t
Analog							
0 - 25	0	13.8	25	5.7	20	8 (9.8)	0.7 (0.7)
25 - 50	25		32				
50 - 75	50	12	49	5.5			
75 - 100	75	14	63				
100 - 125	100	12	79				
125 - 150	125	14.5	94				
150 - 175	150	15.2	106				
175 - 200	175	14.5	118				
200 - 225	200	13.5	130	6	30	12	1
225 - 250	225		143				
250 - 275	250	14.5	156				
275 - 300	275		169				

Note: Data in () applies to those with carbide-faced disks.



Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER**
Bản quyền nội dung thuộc về **Mitutoyo**

Powered by **NAVITECH** | www.navitech.co
www.npower.com.vn