

Measurement example



Optional Accessories

Code No.	Type	Description
264-020	—	USB Input Tool Series USB Keyboard Signal Conversion Type IT-020U
05CZA662	B	Connection cable (1 m)
05CZA663	B	Connection cable (2 m)
06AFM380B	B	USB Input Tool Direct (2 m)
02AZD730G	IP67	U-WAVE-T
02AZD880G	Buzzer	U-WAVE-T
02AZE200	—	U-WAVE-T mounting bracket
02AZD790B	B	Connection cable for U-WAVE-T (160 mm)
02AZE140B	B	Connection cable for U-WAVE-T For foot switch
264-622	IP67	U-WAVE-TM
264-623	Buzzer	U-WAVE-TM
264-626	IP67	U-WAVE-TMB
264-627	Buzzer	U-WAVE-TMB
02AZF310	IP67	Connecting unit for U-WAVE-TM/TMB

Disc Micrometers
SERIES 323

- Measures “root tangent length” of spur gears and helical gears.
- Determination of the root tangent length: refer to “Quick Guide to Precision Measuring Instruments” on page 13-8.
- Equipped with Ratchet Stop for constant measuring force.



323-250-30

SPECIFICATIONS

Metric							
Code No.	Range (mm)	Resolution (mm)	Maximum permissible error J_{MPE} (μ m)	Flatness (μ m)	Parallelism (μ m)	Anvil dia. (mm)	Measurable module
With SPC data output							
323-250-30	0 - 25	0.001	±4	1	4	ø20	0.5 - 6
323-251-30	25 - 50						
323-252-30	50 - 75		±6				
323-253-30	75 - 100						

Inch / Metric							
Code No.	Range (in)	Resolution	Maximum permissible error J_{MPE} (in)	Flatness (in)	Parallelism (in)	Anvil dia. (in)	Measurable module
With SPC data output							
323-350-30	0 - 1	0.00005 in/ 0.001 mm	±0.0002	0.00004	0.0002	ø0.787	0.5 - 6
323-351-30	1 - 2						
323-352-30	2 - 3		±0.0003				
323-353-30	3 - 4						

- Power source: SR44 battery (1 pc.), **938882** included as standard (for operational checks)
 - Battery life: Approx. 2.4 years under normal use
 - Position detection method: Electromagnetic rotary sensor
 - Standard accessories: Setting standard, 1 pc. (except for measuring range 0 to 25 mm (0 to 1 in) models), Spanner (**301336**), 1 pc.
- Note 1: Root tangent length measurement is not available for some types of gears.
Note 2: For functional details, refer to page 02-7.
Optional connection cable is available only for water-proof type (Digimatic model).

DIMENSIONS

Digimatic models up to 75 mm measuring range

Unit: mm

Digimatic models up to 100 mm measuring range

Range (mm)	L	a	b	c	e	f	t
Digimatic (LCD)							
0 - 25	0	9.2	25	4.5	20	8	0.7
25 - 50	25	11	31	5.4			
50 - 75	50	12.2	50	5.5			
75 - 100	75	14	60				



Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của NPOWER
Bản quyền nội dung thuộc về Mitutoyo

Powered by NAVITECH | www.navitech.co
www.npower.com.vn