



**WARNING**

TO AVOID ELECTRIC SHOCK REMOVE TEST LEADS BEFORE OPENING BATTERY COVER. DO NOT OPERATE WITH OPEN BATTERY COVER.

**DROP PROOF**

**RATING** : =1.5Vx4 0.5VA  
BATTERY : AA / R6 / LR6

**F830mA / 1000V / AC50kA min DC50kA min**

**F 11A / 1000V / AC50kA min DC50kA min (MODEL DT4282 ONLY)**

MADE IN JAPAN

電池カバー部  
Front side of Batterycover

**POWER-ON OPTION**

- (HOLD)** : AFS - ON/OFF
- (BUZZER)** : BUZZER - ON/OFF
- (BACKLIGHT)** : BACKLIGHT - ON/OFF
- (CLEAN)** : MEMORY ALL CLEAR 2sec
- (RESET)** : SYSTEM RESET 2sec
- (V)** : STANDARD IMPEDANCE (dBm) DECISION (SELECT)
- (A)** : 0-20mA / 4-20mA DECISION (SELECT)
- (ALL)** : DISPLAY ALL
- (VER)** : VERSION
- (READ)** : SERIAL NUMBER

スタンド裏部  
Back side of Stand

材質 Material	-			承認 Approved by	永井明博		投影法 Projection Method	第一角法		形名 Model	DT4282	
処理 Finish	-			検図 Checked by	瓶子利夫		尺度 Scale	1:1		単位 Unit	mm	
初版 Orig.	2023/10/19	熊井淳二	電池カバー改版	設計 Designed by	熊井淳二		シート Sheet	1 / 1		図番 Draw No.	DT4282A040	
履歴 Sym.	日付 Date	設計 Designed by	注記 Description	初版 Orig.	2012/10/29	瓶子利夫	新規作成			版 Rev.	02	