

Product Information

48 11 J0

Precision Circlip Pliers

For internal circlips in bore holes

- Heavy duty in continuous operation: up to 10 times longer service life compared to turned tips
- With inserted tips for reliable work
- Large contact faces on the tips: no distortion of circlips, easy fitting
- Bolted joint: precise, zero backlash operation of pliers
- Non-slip plastic coating on the handles



General	
Article No.	48 11 J0
EAN	4003773048510
pliers	grey atramentized
Handles	with non-slip plastic coating
Weight	105 g
Dimensions	140 x 52 x 11 mm
Standard	DIN 5256 C
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size of bore	Ø 8 - 13 mm
Tips (diameter)	Ø 0.9 mm

Technical changes and errors excepted

KNIPEX Quality – Made in Germany



www.npower.com.vn

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER**
Bản quyền nội dung thuộc về công ty **KNIPEX**



NPOWER
Powered by
Navitech

CUNG ỨNG NGÀNH HÀNG KIM KHÍ TỔNG HỢP

Máy kim khí, đồ nghề, thiết bị điện và vật tư ngũ kim

WORK LIKE A PRO

ĐỒ THIẾT CHO DÂN THỨ THIẾT

npower.com.vn



NPPOWER.COM.VN

ZALO OFFICIAL ACCOUNT

Product Information

48 11 J1

Precision Circlip Pliers

For internal circlips in bore holes

- Heavy duty in continuous operation: up to 10 times longer service life compared to turned tips
- With inserted tips for reliable work
- Large contact faces on the tips: no distortion of circlips, easy fitting
- Bolted joint: precise, zero backlash operation of pliers
- Non-slip plastic coating on the handles



General

Article No.	48 11 J1
EAN	4003773048527
pliers	grey atramentized
Handles	with non-slip plastic coating
Weight	105 g
Dimensions	140 x 48 x 12 mm
Standard	DIN 5256 C
REACH compliant	does not contain SVHC
RoHS compliant	not applicable

Technical details

Size of bore	Ø 12 - 25 mm
Tips (diameter)	Ø 1.3 mm

Technical changes and errors excepted



Product Information

48 11 J2

Precision Circlip Pliers

For internal circlips in bore holes

- Heavy duty in continuous operation: up to 10 times longer service life compared to turned tips
- With inserted tips for reliable work
- Large contact faces on the tips: no distortion of circlips, easy fitting
- Bolted joint: precise, zero backlash operation of pliers
- Non-slip plastic coating on the handles



General	
Article No.	48 11 J2
EAN	4003773048534
pliers	grey atramentized
Handles	with non-slip plastic coating
Weight	175 g
Dimensions	180 x 46 x 13 mm
Standard	DIN 5256 C
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size of bore	Ø 19 - 60 mm
Tips (diameter)	Ø 1.8 mm

Technical changes and errors excepted





Product Information

48 11 J3

Precision Circlip Pliers

For internal circlips in bore holes

- Heavy duty in continuous operation: up to 10 times longer service life compared to turned tips
- With inserted tips for reliable work
- Large contact faces on the tips: no distortion of circlips, easy fitting
- Bolted joint: precise, zero backlash operation of pliers
- Non-slip plastic coating on the handles



General	
Article No.	48 11 J3
EAN	4003773048541
pliers	grey atramentized
Handles	with non-slip plastic coating
Weight	266 g
Dimensions	225 x 50 x 14 mm
Standard	DIN 5256 C
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size of bore	Ø 40 - 100 mm
Tips (diameter)	Ø 2.3 mm

Technical changes and errors excepted



Product Information

48 11 J4

Precision Circlip Pliers

For internal circlips in bore holes

- Heavy duty in continuous operation: up to 10 times longer service life compared to turned tips
- With inserted tips for reliable work
- Large contact faces on the tips: no distortion of circlips, easy fitting
- Bolted joint: precise, zero backlash operation of pliers
- Non-slip plastic coating on the handles



General	
Article No.	48 11 J4
EAN	4003773048558
pliers	grey atramentized
Handles	with non-slip plastic coating
Weight	580 g
Dimensions	320 x 46 x 17 mm
Standard	DIN 5256 C
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size of bore	Ø 85 - 140 mm
Tips (diameter)	Ø 3.2 mm

Technical changes and errors excepted

