

Product Information

71 01 160

KNIPEX CoBolt® S
 Compact Bolt Cutters

- Extremely high cutting performance in a convenient length of 160 mm
- Small, slim head for excellent accessibility
- Compact and powerful: cuts bolts, nails, rivets etc.
- Heavy duty, induction-hardened cutting edge for thin, hard wire, screws and springs. Cutting edge hardness approx. 64 HRC
- Less physical effort due to efficient lever action mechanism
- No slipping of the material to be cut due to lasered cutting edge
- With gripping surface below the joint for gripping and pulling wires from Ø 1.0 mm



General	
Article No.	71 01 160
EAN	4003773082668
pliers	black atramentized
Handles	plastic coated
Weight	200 g
Dimensions	160 x 45 x 14 mm
REACH compliant	contains SVHC
RoHS compliant	not applicable
Technical details	
Cutting capacities soft wire (diameter)	Ø 5 mm
Cutting capacities medium hard wire (diameter)	Ø 4.4 mm
Cutting capacities hard wire (diameter)	Ø 3.2 mm
Cutting capacities piano wire (diameter)	Ø 3.0 mm

Technical changes and errors excepted

www.npower.com.vn

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER**
 Bản quyền nội dung thuộc về công ty **KNIPEX**




Powered by **NAVITECH** | www.navitech.co



Product Information

71 31 160

KNIPEX CoBolt® S

Compact Bolt Cutters

With recess in the cutting edge

- Extremely high cutting performance in a convenient length of 160 mm
- Small, slim head for excellent accessibility
- Compact and powerful: cuts bolts, nails, rivets etc.
- Heavy duty, induction-hardened cutting edge for thin, hard wire, screws and springs. Cutting edge hardness approx. 64 HRC
- Less physical effort due to efficient lever action mechanism
- No slipping of the material to be cut due to lasered cutting edge
- With gripping surface below the joint for gripping and pulling wires from Ø 1.0 mm
- Blades with recess for easier cutting of larger cross-sections thanks to better leverage close to the fulcrum



General	
Article No.	71 31 160
EAN	4003773084587
pliers	black atramentized
Handles	plastic coated
Weight	200 g
Dimensions	160 x 45 x 14 mm
REACH compliant	contains SVHC
RoHS compliant	not applicable
Technical details	
Cutting capacities soft wire (diameter)	Ø 5 mm
Cutting capacities medium hard wire (diameter)	Ø 4.8 mm
Cutting capacities hard wire (diameter)	Ø 3.6 mm
Cutting capacities piano wire (diameter)	Ø 3.3 mm

Technical changes and errors excepted



