

Product Information

71 82 950

Concrete Mesh Cutter



- Robust cutting edges are additionally induction-hardened, cutting edge hardness approx. 62 HRC
- Forged-in stopper with comfortable shock- absorber

• Cutting capacity up to 48 HRC hardness

- Good access due to very flat construction of head and joint area
- Sturdy non-slip two-colour multi-component handle sleeves
- Precise adjustment (12 positions) by eccentric bolt
- High cutting performance with minimum effort due to optimum coordination
 of the cutting edge angle and transmission ratio
- Bolted cutter head, replaceable





General	
Article No.	71 82 950
EAN	4003773066798
Head	grey atramentized
Handles	with multi-component handles
Weight	4,110 g
Dimensions	950 x 180 x 40 mm
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	

Technical details	
HRC 19	Ø 11 mm
HRC 40	Ø 9 mm
HRC 48	Ø 6 mm
Cutting edge length mm	44 mm
Head thickness	40 mm

Technical changes and errors excepted

www.npower.com.vn

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER** Bản quyền nội dung thuộc về công ty **KNIPEX**





KNIPEX Quality – Made in Germany















KNIPEX Quality – Made in Germany





