


74 01 140

High Leverage Diagonal Cutter



- High cutting performance with minimum effort due to optimum coordination of the cutting edge angle and transmission ratio
- Precision cutting edges also induction-hardened (hardness approx. 64 HRC), for all wire types including piano wire





General		
Article No.	74 01 140	
EAN	4003773039747	
pliers	black atramentized	
Head	polished	
Handles	plastic coated	
Weight	131 g	
Dimensions	140 x 52 x 15 mm	
Standard	DIN ISO 5749	
REACH compliant	does not contain SVHC	
RoHS compliant	not applicable	
Technical details		
Cutting capacities soft wire (diameter)	Ø	
Cutting capacities medium hard wire (diameter)	Ø 3.1 mm	
Cutting capacities hard wire (diameter)	Ø 2.0 mm	
Cutting capacities piano wire (diameter)	Ø 1.5 mm	













www.npower.com.vn

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER** Bản quyền nội dung thuộc về công ty **KNIPEX**








74 01 160

High Leverage Diagonal Cutter



- High cutting performance with minimum effort due to optimum coordination of the cutting edge angle and transmission ratio
- Precision cutting edges also induction-hardened (hardness approx. 64 HRC), for all wire types including piano wire





General		
Article No.	74 01 160	
EAN	4003773033141	
pliers	black atramentized	
Head	polished	
Handles	plastic coated	
Weight	178 g	
Dimensions	160 x 53 x 16 mm	
Standard	DIN ISO 5749	
REACH compliant	does not contain SVHC	
RoHS compliant	not applicable	
Technical details		
Cutting capacities soft wire (diameter)	Ø	
Cutting capacities medium hard wire (diameter)	Ø 3.4 mm	
Cutting capacities hard wire (diameter)	Ø 2.5 mm	
Cutting capacities piano wire (diameter)	Ø 2.0 mm	














74 01 180

High Leverage Diagonal Cutter



- High cutting performance with minimum effort due to optimum coordination of the cutting edge angle and transmission ratio
- Precision cutting edges also induction-hardened (hardness approx. 64 HRC), for all wire types including piano wire





General		
Article No.	74 01 180	
EAN	4003773022008	
pliers	black atramentized	
Head	polished	
Handles	plastic coated	
Weight	241 g	
Dimensions	180 x 49 x 16 mm	
Standard	DIN ISO 5749	
REACH compliant	does not contain SVHC	
RoHS compliant	not applicable	
Technical details		
Cutting capacities soft wire (diameter)	Ø	
Cutting capacities medium hard wire (diameter)	Ø 3.8 mm	
Cutting capacities hard wire (diameter)	Ø 2.7 mm	
Cutting capacities piano wire (diameter)	Ø 2.2 mm	














74 01 200

High Leverage Diagonal Cutter



- High cutting performance with minimum effort due to optimum coordination of the cutting edge angle and transmission ratio
- Precision cutting edges also induction-hardened (hardness approx. 64 HRC), for all wire types including piano wire





General		
Article No.	74 01 200	
EAN	4003773034056	
pliers	black atramentized	
Head	polished	
Handles	plastic coated	
Weight	263 g	
Dimensions	200 x 47 x 15 mm	
Standard	DIN ISO 5749	
REACH compliant	does not contain SVHC	
RoHS compliant	not applicable	
Technical details		
Cutting capacities soft wire (diameter)	Ø	
Cutting capacities medium hard wire (diameter)	Ø 4.2 mm	
Cutting capacities hard wire (diameter)	Ø 3.0 mm	
Cutting capacities piano wire (diameter)	Ø 2.5 mm	















74 01 250

High Leverage Diagonal Cutter

- For very tough, continuous use
- High cutting performance with minimum effort due to optimum coordination of the cutting edge angle and transmission ratio
- Precision cutting edges also induction-hardened (hardness approx. 64 HRC), for all wire types including piano wire





General		
Article No.	74 01 250	
EAN	4003773034063	
pliers	black atramentized	
Head	polished	
Handles	plastic coated	
Weight	391 g	
Dimensions	250 x 54 x 16 mm	
Standard	DIN ISO 5749	
REACH compliant	does not contain SVHC	
RoHS compliant	not applicable	
Technical details		
Cutting capacities soft wire (diameter)	Ø	
Cutting capacities medium hard wire (diameter)	Ø 4.6 mm	
Cutting capacities hard wire (diameter)	Ø 3.5 mm	
Cutting capacities piano wire (diameter)	Ø 3.0 mm	









