

Product Information

95 36 250

Cable Cutter
(ratchet action)



1000V

- Little handforce required due to very high transmission ratio
- Simple handling as a result of low weight and compact design - can be used even in confined areas
- Durchtrennt Cu- und Al-Kabel bis zu einem Durchmesser von 32 mm (240 mm²) im Ein- und Zweihandbetrieb
- Not suitable for steel wire, wire ropes and fine-stranded (highly flexible) conductors
- Precision-ground, hardened blades
- Clean and smooth cut without crushing and deformation
- One-hand operation using ratchet principle
- Two-stage ratchet drive for easy cutting
- Pinch guard prevents operators' fingers being pinched

General	
Article No.	95 36 250
EAN	4003773026884
pliers	black lacquered
Handles	insulated with multi-component grips, VDE-tested
Weight	652 g
Dimensions	250 x 115 x 20 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Cutting capacity copper cable, multiple-stranded	240 mm²
Cutting capacity copper cable, multiple-stranded	Ø 32 mm
MCM	500
VDE tested	yes

Technical changes and errors excepted

www.npower.com.vn

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER**
 Bản quyền nội dung thuộc về công ty **KNIPEX**





Product Information

95 36 280

Cable Cutter (ratchet action)



⚡ 1000V 



- Little handforce required due to very high transmission ratio
- Simple handling as a result of low weight and compact design - can be used even in confined areas
- Durchtrennt Cu- und Al-Kabel bis zu einem Durchmesser von 52 mm (380 mm²) im Ein- und Zweihandbetrieb
- Not suitable for steel wire, wire ropes and fine-stranded (highly flexible) conductors
- Precision-ground, hardened blades
- Clean and smooth cut without crushing and deformation
- One-hand operation using ratchet principle
- Two-stage ratchet drive for easy cutting
- Pinch guard prevents operators' fingers being pinched
- Suitable for aluminium sector cable up to 4 x 150 mm²

General	
Article No.	95 36 280
EAN	4003773026891
pliers	black lacquered
Handles	insulated with multi-component grips, VDE-tested
Weight	835 g
Dimensions	280 x 135 x 28 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Cutting capacity copper cable, multiple-stranded	380 mm ²
Cutting capacity copper cable, multiple-stranded	Ø 52 mm
MCM	750
VDE tested	yes

Technical changes and errors excepted

