

Product Information

97 52 65 DG A

Four-Mandrel Crimping Pliers for turned con-  
tacts



- For crimping turned contacts
- Four-mandrel crimping for top-quality crimp connections
- Mandrel gauge to check the basic setting
- Repetitive, high crimping quality due to ratchet mechanism (unlockable)
- Optimum transmission of force due to highly effective lever action for fa-  
tigue-reduced operation
- High operation comfort thanks to handy shape
- Crimping capacity can be adjusted in increments of 0.01 mm
- With digital display of the preset crimping capacities and possibility of re-cal-  
ibration via RESET function with electronic wear monitoring
- Adjustment in mm, inches or comparable selection positions according to MIL
- With table for calculating the settings
- Pliers in a plastic case with foam insert
- Without locator

General	
Article No.	97 52 65 DG A
EAN	4003773071990
pliers	chrome-plated
Head	chrome-plated
Handles	with multi-component handles
Weight	633 g
Dimensions	250 x 86 x 19 mm
REACH compliant	contains SVHC
RoHS compliant	not applicable
Technical details	
Application	turned contacts (Harting; Ilme; Phoenix; Amphenol; Walther; HTS; Contact; Weidmüller)
Capacity in square millimetres	0.14 – 6 mm <sup>2</sup>
AWG	26 – 10
Number of crimp profiles	1
Max. contact diameter	7.5 mm

Technical changes and errors excepted

[www.npower.com.vn](http://www.npower.com.vn)

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER**  
 Bản quyền nội dung thuộc về công ty **KNIPEX**





Product Information

97 52 65 DG

Four-Mandrel Crimping Pliers for turned con-  
tacts



- For crimping turned contacts
- Four-mandrel crimping for top-quality crimp connections
- Mandrel gauge to check the basic setting
- Repetitive, high crimping quality due to ratchet mechanism (unlockable)
- Optimum transmission of force due to highly effective lever action for fa-  
tigue-reduced operation
- High operation comfort thanks to handy shape
- Crimping capacity can be adjusted in increments of 0.01 mm
- With digital display of the preset crimping capacities and possibility of re-cal-  
ibration via RESET function with electronic wear monitoring
- Adjustment in mm, inches or comparable selection positions according to MIL
- With table for calculating the settings
- Pliers in a plastic case with foam insert and standard locator for precise  
positioning of the contacts



General	
Article No.	97 52 65 DG
EAN	4003773063216
pliers	chrome-plated
Head	chrome-plated
Handles	with multi-component handles
Weight	633 g
Dimensions	250 x 86 x 19 mm
REACH compliant	contains SVHC
RoHS compliant	not applicable
Technical details	
Application	turned contacts (Harting; Ilme; Phoenix; Amphenol; Walther; HTS; Contact; Weidmüller)
Capacity in square millimetres	0.14 – 6 mm²
AWG	26 – 10
Number of crimp profiles	1
Max. contact diameter	7.5 mm

Technical changes and errors excepted



