

Product Information

97 52 04

Crimping Pliers

For two-hand operation

- For solder-free electrical connections
- The ingenious lever transmission reduces the handforce up to 30% compared with regular crimping pliers
- Consistently high crimping quality due to precision dies and ratchet mechanism (unlockable)
- Precise, factory calibrated crimping pressure
- Two-hand operation for easy crimping of large conductor diameters
- Easy handling as a result of well balanced centre of gravity, angled head and ergonomically shaped handles
- Crimping die is not exchangeable



General	
Article No.	97 52 04
EAN	4003773025450
pliers	burnished
Head	burnished
Handles	with non-slip plastic grips
Weight	562 g
Dimensions	250 x 82 x 27 mm
REACH compliant	contains SVHC
RoHS compliant	not applicable
Technical details	
Application	non-insulated open plug type connectors (plug width 2.8 + 4.8 mm)
Capacity in square millimetres	0.1 – 2.5 mm²
Number of crimp profiles	4
AWG	26 – 14

Technical changes and errors excepted

www.npower.com.vn

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER**
 Bản quyền nội dung thuộc về công ty **KNIPEX**





Product Information

97 52 05

Crimping Pliers

For two-hand operation

- For solder-free electrical connections
- The ingenious lever transmission reduces the handforce up to 30% compared with regular crimping pliers
- Consistently high crimping quality due to precision dies and ratchet mechanism (unlockable)
- Precise, factory calibrated crimping pressure
- Two-hand operation for easy crimping of large conductor diameters
- Easy handling as a result of well balanced centre of gravity, angled head and ergonomically shaped handles
- Crimping die is not exchangeable



General	
Article No.	97 52 05
EAN	4003773025467
pliers	burnished
Head	burnished
Handles	with non-slip plastic grips
Weight	572 g
Dimensions	250 x 83 x 24 mm
REACH compliant	contains SVHC
RoHS compliant	not applicable
Technical details	
Application	non-insulated open plug type connectors - plug width 4.8 + 6.3 mm
Capacity in square millimetres	0.5 – 6 mm ²
Number of crimp profiles	3
AWG	20 – 10

Technical changes and errors excepted

