

Product Information

98 24 01 SL

Screwdriver (Slim) for cross-recessed screws

Phillips®

- Reduced extra slim shaft in the front area for recessed spring and screw elements
- Ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- Handle design prevents rolling



1000V

General	
Part No.	98 24 01 SL
EAN	4003773079750
point	burnished
Handles	insulating multi-component handle, VDE-tested
Weight	58 g
Dimensions	187 x 30 x 30 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size	PH1
Blade length	80 mm
Handle length	107 mm
Length of non-insulated blade	15 mm
VDE tested	yes

Technical changes and errors excepted

www.npower.com.vn

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER**
 Bản quyền nội dung thuộc về **KNIPEX**



Product Information

98 24 02 SL

Screwdriver (Slim) for cross-recessed screws

Phillips®

- Reduced extra slim shaft in the front area for recessed spring and screw elements
- Ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- Handle design prevents rolling



1000V

General	
Part No.	98 24 02 SL
EAN	4003773079767
point	burnished
Handles	insulating multi-component handle, VDE-tested
Weight	94 g
Dimensions	212 x 33 x 35 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size	PH2
Blade length	100 mm
Handle length	112 mm
Length of non-insulated blade	18 mm
VDE tested	yes

Technical changes and errors excepted