

Product Information

98 25 00

Screwdriver for cross recessed screws

Pozidriv®

- Ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- Handle design prevents rolling




⚡ 1000V

General	
Part No.	98 25 00
EAN	4003773062370
point	burnished
Handles	insulating multi-component handle, VDE-tested
Weight	32 g
Dimensions	162 x 25 x 25 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size	PZ0
Blade length	60 mm
Handle length	102 mm
Blade Ø	3.0 mm
Length of non-insulated blade	15 mm
VDE tested	yes

Technical changes and errors excepted

www.npower.com.vn

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER**
Bản quyền nội dung thuộc về **KNIPEX**



Product Information

98 25 01

Screwdriver for cross recessed screws

Pozidriv®

- Ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- Handle design prevents rolling



⚡ 1000V ⚡

General	
Part No.	98 25 01
EAN	4003773031260
point	burnished
Handles	insulating multi-component handle, VDE-tested
Weight	58 g
Dimensions	187 x 28 x 30 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size	PZ1
Blade length	80 mm
Handle length	107 mm
Blade Ø	4.5 mm
Length of non-insulated blade	15 mm
VDE tested	yes

Technical changes and errors excepted

Product Information

98 25 02

Screwdriver for cross recessed screws

Pozidriv®

- Ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- Handle design prevents rolling



⚡ 1000V ⚡

General	
Part No.	98 25 02
EAN	4003773031277
point	burnished
Handles	insulating multi-component handle, VDE-tested
Weight	90 g
Dimensions	212 x 35 x 32 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size	PZ2
Blade length	100 mm
Handle length	112 mm
Blade Ø	6.0 mm
Length of non-insulated blade	18 mm
VDE tested	yes

Technical changes and errors excepted

Product Information

98 25 03

Screwdriver for cross recessed screws

Pozidriv®

- Ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- Handle design prevents rolling



⚡ 1000V ⚡

General

Part No.	98 25 03
EAN	4003773031284
point	burnished
Handles	insulating multi-component handle, VDE-tested
Weight	167 g
Dimensions	270 x 39 x 40 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable

Technical details

Size	PZ3
Blade length	150 mm
Handle length	120 mm
Blade Ø	8.0 mm
Length of non-insulated blade	18 mm
VDE tested	yes

Technical changes and errors excepted

Product Information

98 25 04

- Ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- Handle design prevents rolling

Screwdriver for cross recessed screws

Pozidriv®



⚡ 1000V

General	
Part No.	98 25 04
EAN	4003773062387
point	burnished
Handles	insulating multi-component handle, VDE-tested
Weight	245 g
Dimensions	320 x 37 x 36 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Size	PZ4
Blade length	200 mm
Handle length	120 mm
Blade Ø	10.0 mm
Length of non-insulated blade	18 mm
VDE tested	yes

Technical changes and errors excepted