

Product Information

99 11 250

High Leverage Concreters' Nipper

High lever transmission

- 25% less effort required compared to conventional concreters' nippers of the same size
- Extra-slim form for tying deep mounted steel rods
- To lace concrete reinforcing steel with binding wire from a roll
- Wire is twisted and cut in a single pass
- High-leverage joint, minimising strain, even when thick binding wires are used
- The high damping of the cutting stroke on cutting through the binding wire reduces the strain on tendons and muscles
- Cutting edges additionally hardened; cutting edge hardness approx. 61 HRC




General	
Article No.	99 11 250
EAN	4003773071402
pliers	black atramentized
Head	polished
Handles	plastic coated
Weight	429 g
Dimensions	250 x 47 x 23 mm
Standard	DIN ISO 9242
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Cutting capacities medium hard wire (diameter)	Ø 1.8 mm
Cutting capacities medium hard wire (diameter)	Ø 3.3 mm
Head width (W3)	25.0 mm
Cutting edge length mm	23.0 mm

Technical changes and errors excepted

www.npower.com.vn

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER**
Bản quyền nội dung thuộc về công ty **KNIPEX**



Powered by **NAVITECH** | www.navitech.co

Product Information

99 11 300

High Leverage Concreters' Nipper

High lever transmission

- 25% less effort required compared to conventional concreters' nippers of the same size
- Extra-slim form for tying deep mounted steel rods
- To lace concrete reinforcing steel with binding wire from a roll
- Wire is twisted and cut in a single pass
- High-leverage joint, minimising strain, even when thick binding wires are used
- The high damping of the cutting stroke on cutting through the binding wire reduces the strain on tendons and muscles
- Cutting edges additionally hardened; cutting edge hardness approx. 61 HRC



General

Article No.	99 11 300
EAN	4003773042365
pliers	black atramentized
Head	polished
Handles	plastic coated
Weight	537 g
Dimensions	300 x 52 x 17 mm
Standard	DIN ISO 9242
REACH compliant	does not contain SVHC
RoHS compliant	not applicable

Technical details

Cutting capacities medium hard wire (diameter)	Ø 2.0 mm
Cutting capacities medium hard wire (diameter)	Ø 3.8 mm
Head width (W3)	25.0 mm
Cutting edge length mm	25.0 mm

Technical changes and errors excepted

