

SANDING

Pneumatic Compact Sander


ORBITAL SANDER

Model OSV-60A 



Random orbital action creates a professional finish

By offsetting the sanding pad shaft, fast aggressive sanding is achieved while dramatically reducing swirl patterns. Speed adjustments allow for the best speed for the best job.



Heavy-duty and powerful with adjustable speed regulator

- Powerful dual action for tough applications
- Standard with dust extraction system
- Rugged construction for years of reliable performance



Specifications

Model	OSV-60A	
Air Pressure	MPa (kgf/cm ²)	0.6 (6)
Air Consumption (No-load)	m ³ /min	0.68
Free Speed	min ⁻¹ (rpm)	8500
Orbit Diameter	mm	10
Paper Size	mm	150 (6")
Installed Pad Type		Leather for PSA with 6 holes
Air Inlet Size		Rc 1/4
Mass (Weight)	kg	2
Accessories Included		<ul style="list-style-type: none"> • Dust Collection Ass'y with Dust Bag • Single Ended Spanner 17 • Bushing R 1/4 x NPT 1/4 • Brush

Pad for OSV-60A

PN	Description	Sales Unit
TB03898	Pad 6" L-6H Ass'y (Leather type)	1 set

Pneumatic Compact Sander


PALM ORBITAL SANDER

Model APS-125 



Random orbital action creates a professional finish

By offsetting the sanding pad shaft, fast aggressive sanding is achieved while dramatically reducing swirl patterns. Speed adjustments allow for the best speed for the best job.



Ergonomic lightweight design

- Extremely light. APS-125 weighs just 690 g
- Ergonomically designed for operator convenience and comfort
- Powerful high speed 10000 RPM motor
- Ultra small orbital action for high quality swirl-free finishes
- Available with 125 mm or 150 mm pads
- Variable speed control

Applications

- Feather edging, metal preparation, and finishing work on body filler
- Curved surface sanding and corner rounding in wood work

Specifications

Model	APS-125		APS-150
	NVL5H	NVV5H	
Air Pressure	MPa (kgf/cm ²)	0.6 (6)	
Air Consumption (No-load)	m ³ /min	0.45	
Free Speed	min ⁻¹ (rpm)	10000	
Orbit Diameter	mm	5	
Paper Size	mm	125 (5")	150 (6")
Installed Pad Type	Leather with 5 holes	Velcro with 5 holes	Velcro with 6 holes
Air Inlet Size		Rc 1/4	
Mass (Weight)	kg	0.69	0.72
Accessories Included	<ul style="list-style-type: none"> • 17 mm Single Ended Spanner • Bushing R 1/4 x NPT 1/4 		

Pads for APS-125/APS-150

PN	Description	Sales Unit	Model
TB03669	Pad 5" V-5H Ass'y (Velcro type)	1 set	APS-125
TB03801	Pad 5" L-5H Ass'y (Leather type)		
TB03650	Pad 6" V-6H Ass'y (Velcro type)		APS-150

For Self Vacuum & Central Vacuum

The non-vacuum model is available from stock and can easily be modified to the self-vacuum or central vacuum type.

Self Vacuum



Optional parts required for adding Self Vacuum function

- TQ04685 Stopper
- TB03594 Ejector Ass'y
- LO02848 P Tapping Screw
- TA99239 Hose Ass'y
- TP14836 Dust Bag

Central Vacuum



Optional parts required for adding Central Vacuum function

- TQ04682 Ejector
- LO02848 P Tapping Screw

