SANDING

Pneumatic Belt Sander

BABY BELTON

Ideal for deburring, chamfering, bead grinding, and polishing applications


- · Compact and lightweight, yet powerful
- Alternative rotation direction
- Ergonomically designed for left or right hand operator convenience




Specifications				
Model		BB-10B Lever Switch Type	BB-10B Ring Switch Type	BB-20
Air Pressure	MPa (kgf/cm²)			
Air Consumption (No-load) m³/min	0.20		0.43
Free Speed	min ⁻¹ (rpm)	17000		16000
Belt Speed	m/min	1120		1160
Belt Size	mm	10 x 330		20 x 330
Air Inlet Size				
Mass (Weight)	kg	0.60	0.50	0.80
Installed Abrasive Belt		Z#100 x 10 mm	Z#100 x 10 mm	Z#60 x 20 mm
Accessories Included		Abrasive Belt Z#100 x 10 mm (Installed) Abrasive Belt Z#120 x 10 mm Abrasive Belt Z#180 x 10 mm Abrasive Belt Z#180 x 10 mm Abrasive Belt Z#240 x 10 mm 1.5 mm Hex Socket Screw Key Bushing R 1/4 x NPT 1/4 Offset Bracket Ass'y (Installed)	Abrasive Belt Z#100 x 10 mm (Installed) Abrasive Belt Z#120 x 10 mm Abrasive Belt Z#180 x 10 mm Abrasive Belt Z#240 x 10 mm 1.5 mm Hex Socket Screw Key Bushing R 1/4 x NPT 1/4 Offset Bracket Ass'y (Installed)	Abrasive Belt Z#60 x 20 mm (Installed) Abrasive Belt Z#120 x 20 mm Abrasive Belt Z#240 x 20 mm 2.5 mm Hex Socket Screw Key 3 mm Hex Socket Screw Key Shoe Dust Cover Bushing R 1/4 x NPT 1/4















Easy switching of belt rotation direction (BB-10B)

By adjusting the lever of the FR valve, the rotation direction of the abrasive belt can be changed. The direction of the chip ejection can be changed by switching the rotation direction. The rotation speed can also be adjusted by the angle of the lever.

Controlling the chip ejection direction





Adjusting FR Valve

The rotation speed can also be adjusted by the angle of the lever.





Forward (right)

Reverse (left)


Guard position is adjustable (BB-20)

Guard angle can be changed freely in accordance with the working position and shape of the workpieces.



Belt Speed Adjustment (BB-20)

Belt speed can be easily adjusted by turning the adjust valve without a tool.



Ideal for deburring, chamfering, bead grinding, and polishing applications







Optional P	arts			
Ref. No.	PN	Description	Sales Unit	Model
1	TB10549	Offset Bracket Ass'y	1 set	BB-10B
2	TB07109	Offset Bracket 20 Ass'y	1 set	
3	TB07224	Tension Bar 520 Ass'y*	1 set	BB-20
4	TQ10701	Shoe 520*	1 piece	DD-20
5	TB07227	Finger Pad Ass'y 520	1 set	











*TB07224 and TQ10701 are used together.

Grit	PN			
	Zirconia (Z)	Alumina (AA)	Ceramic (CE)	
#40	3	-	TB10943	
#60	TB10904	-	TB10944	
#80	TB10905	-	TB10945	
#100	TB10906	-	TB10946	
#120	TB10907	-	TB10947	
#180	TB10908	-	35/	
#240	TB10909	-		
#400		TB10936		

Belt Size : <mark>20</mark> mm x <mark>330</mark> mm (W x L)						
Grit	PN					
	Zirconia (Z)	Alumina (AA)	Ceramic (CE)	Non-woven		
#40		-	-	-		
#60	TB10930		TB10958	-		
#80	TB10931	-	TB10959	-		
#100	TB10932	3=3	TB10960	-		
#120	TB10933	-	TB10961	-		
#180	TB10934	5.5	-	TB11047 A-M Equivalent to #180		
#240	TB10935		-	-		
#320	-	-	-	TB11046 A-VF Equivalent to #320		
#400	-	TB10942	-	TB11048 S-SF Equivalent to #400		
	20 pcs./set	20 pcs./set	20 pcs./set	5 pcs./set		
Sales Unit	Garon	T. E. C. T.	a distant	Carlon.		