Handy Pneumatic Sander

FREE SANDER

Super lightweight, low-vibration design

- · Ideal for sanding and surface finishing wood, metal, plastic and other materials
- · Lightweight design with minimal vibration
- High output and low air consumption motors produce high speed orbits for swirl-free finishes
- · Oil free design
- · Suitable for industrial and production applications


Model FS-50A C€







The pad is made of sponge rubber and conforms easily to the shape being worked. Double-stick tape is used with round pad.



	Optional Accessories				
100 mm	Ref. No.	PN	Description	Sales	
	1	TA99828	Rubber Pad	1 pi	
	2	TA9A367	Rubber Pad		
	•			1 pi	

Model		FS-50A	FS-100C	
Air Pressure MPa (kgf/cm²)		0.6 (6)		
Air Consumption (No-load) m3/min		0.14	0.20	
Free Speed	min ⁻¹ (rpm)	15000	20000	
Orbit Diameter	mm	1.2	1.5	
Pad Size	mm	75 x 82	110 x 100	
Paper Size	mm	70 x 114	114 x 140	
Air Inlet Size		Rc 1/8		
Mass (Weight)	kg	0.50		
• Air Hose H Ass'y • Sanding Paper #240, #180 (5 pieces • Bushing R 1/4 x NPT 1/4		nding Paper #240, #180 (5 pieces of each)		

Ref. No.	Accessor	Description	Sales Unit	Model	
1	1 TA99828 Rubber Pad		1 piece	FS-50A	
2	TA9A367	Rubber Pad		. 2 00/1	
3	TA91474	Round Pad	1 piece		
TA9A266	Sanding Paper #100		FS-100C		
	Sanding Paper #120				
	Sanding Paper #150				
4	TA9A268	Sanding Paper #180	200 pcs./set		
TA9A269 TA9A270 TA9A271	Sanding Paper #240				
	Sanding Paper #280				
	Sanding Paper #320				



Pneumatic Reciprocating Sander

LINE SANDER

Ideal for inline and grain sanding applications

- · Ideal for most inline and profile sanding applications
- · Compact and lightweight 0.75 kg design
- · Low vibration and minimal noise output
- · Suitable for sanding steel, aluminum, wood, plastic and other materials



Model		LS-10
Air Pressure	MPa (kgf/cm²)	0.6 (6)
Air Consumption (No-I	oad) m³/min	0.11
Strokes per Minute	min ⁻¹	4000
Stroke Length	mm	4
Pad Size	mm	55 x 103
Paper Size	mm	57 x 140
Air Inlet Size		Rc 1/8
Mass (Weight)	kg	0.75
Accessories Include	d	Air Hose E Ass'y Block Rubber Pad Base Plate A Ass'y Sanding Paper #240, #320 (5 pieces of each) Bushing R 1/4 x NPT 1/4





The Block Rubber Pad Assembly can be easily trimmed to conform to the shape being worked and is available as an accessory.



Cut standard size paper (9" x 11") into 8 pieces, as shown below. For dry sanding, use an open coat abrasive paper with silicon carbide or aluminum oxide abrasive grains to prevent clogging, improve grinding efficiency, and prolong the life of

\vdash	11	"
	1/8	
6		

Ref. No.	PN	Description	Sales Unit
1	TA96665	Rubber Pad	4
2 TA96739		Block Rubber Pad	1 piece
1		2	



Optional Accessories







