

# SANDING

Pneumatic Compact Sander

## ORBITAL SANDER

Model **OSV-60A** 


**Heavy-duty and powerful with adjustable speed regulator**

- Powerful dual action for tough applications
- Standard with dust extraction system
- Rugged construction for years of reliable performance



Random orbital action creates a professional finish

By offsetting the sanding pad shaft, fast aggressive sanding is achieved while dramatically reducing swirl patterns. Speed adjustments allow for the best speed for the best job.



### Specifications

Model	OSV-60A	
Air Pressure	MPa (kgf/cm <sup>2</sup> )	0.6 (6)
Air Consumption (No-load)	m <sup>3</sup> /min	0.68
Free Speed	min <sup>-1</sup> (rpm)	8500
Orbit Diameter	mm	10
Paper Size	mm	150 (6")
Installed Pad Type	Leather for PSA with 6 holes	
Air Inlet Size	Rc 1/4	
Mass (Weight)	kg	2
Accessories Included	<ul style="list-style-type: none"> <li>• Dust Collection Ass'y with Dust Bag</li> <li>• Single Ended Spanner 17</li> <li>• Bushing R 1/4 x NPT 1/4</li> <li>• Brush</li> </ul>	

### Pad for OSV-60A

PN	Description	Sales Unit
TB03898	Pad 6" L-6H Ass'y (Leather type)	1 set

Pneumatic Compact Sander

## PALM ORBITAL SANDER


Model **APS-125** 

Model **APS-150** 



Random orbital action creates a professional finish

By offsetting the sanding pad shaft, fast aggressive sanding is achieved while dramatically reducing swirl patterns. Speed adjustments allow for the best speed for the best job.



### Ergonomic lightweight design

- Extremely light. APS-125 weighs just 690 g
- Ergonomically designed for operator convenience and comfort
- Powerful high speed 10000 RPM motor
- Ultra small orbital action for high quality swirl-free finishes
- Available with 125 mm or 150 mm pads
- Variable speed control

### Applications

- Feather edging, metal preparation, and finishing work on body filler
- Curved surface sanding and corner rounding in wood work

### Specifications

Model	APS-125		APS-150
	NVL5H	NVV5H	
Air Pressure	MPa (kgf/cm <sup>2</sup> )	0.6 (6)	
Air Consumption (No-load)	m <sup>3</sup> /min	0.45	
Free Speed	min <sup>-1</sup> (rpm)	10000	
Orbit Diameter	mm	5	
Paper Size	mm	125 (5")	150 (6")
Installed Pad Type	Leather with 5 holes	Velcro with 5 holes	Velcro with 6 holes
Air Inlet Size	Rc 1/4		
Mass (Weight)	kg	0.69	0.72
Accessories Included	• 17 mm Single Ended Spanner • Bushing R 1/4 x NPT 1/4		

### Pads for APS-125/APS-150

PN	Description	Sales Unit	Model
TB03669	Pad 5" V-5H Ass'y (Velcro type)	1 set	APS-125
TB03801	Pad 5" L-5H Ass'y (Leather type)		APS-150
TB03650	Pad 6" V-6H Ass'y (Velcro type)		

### For Self Vacuum & Central Vacuum

The non-vacuum model is available from stock and can easily be modified to the self-vacuum or central vacuum type.

#### Self Vacuum



Optional parts required for adding Self Vacuum function

TQ04685 Stopper  
TB03594 Ejector Ass'y  
LQ02848 P Tapping Screw  
TA99239 Hose Ass'y  
TP14836 Dust Bag

#### Central Vacuum



Optional parts required for adding Central Vacuum function

TQ04682 Ejector  
LQ02848 P Tapping Screw



Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER** Bản quyền nội dung thuộc về **NITTO KOHKI**

[www.npower.com.vn](http://www.npower.com.vn) Powered by **NAVITECH** | [www.navitech.co](http://www.navitech.co)