

# INSTRUCTION MANUAL

## PNEUMATIC CHIPPING HAMMER

Please read this manual carefully before you attempt to use your tool so that you may use it properly and safely.

### AIR CHIPPER Model ACH-16 CH-24 PROFESSIONAL TOOL



ACH-16



CH-24

### Specifications

Model		ACH-16	CH-24
Maximum Operating Pressure	MPa	0.6	
Air Consumption (No Load)	m <sup>3</sup> /min	0.15	0.20
Stroke Speed (No Load)	r/min (min <sup>-1</sup> )	6000	4000
Chisel Shank	mm	O.D.10.5	12.7sq.
Mass (Weight)	kg	0.9	1.7
Sound Pressure Level	dB(A)	87	88
Sound Power Level	dB(A)	98	99
Vibration Level [Uncertainty K]	m/s <sup>2</sup> [m/s <sup>2</sup> ]	66 [7.0]	100 [10.5]
Thread Size of Air Inlet		Rc3/8	

Due to continuous product development/improvement the specifications and configurations in this document are subject to change without prior notice.

Manufactured by :



**NITTO KOHKI Co., Ltd.**

2-9-4, Nakaikegami, Ohta-ku,  
Tokyo, 146-8555, Japan  
Tel : (81)-3-3755-1111  
Fax : (81)-3-3753-8791  
E-mail : overseas@nitto-kohki.co.jp  
URL : www.nitto-kohki.co.jp

**Keep the manual handy – so you can use it whenever necessary.**

Original Instructions

TQ12815-5 03/2020

Tài liệu được tổng hợp bởi đội ngũ kỹ thuật của **NPOWER** Bản quyền nội dung thuộc về **NITTO KOHKI**

[www.npower.com.vn](http://www.npower.com.vn) Powered by **NAVITECH** | [www.navitech.co](http://www.navitech.co)

Thank you very much for your purchase of this **Nitto Kohki products**.

Before using your tool, please read this manual carefully so that you may use it properly to get the most out of it.

**Please keep the manual handy - so you can use it whenever necessary.**

- **English** : Please ask your dealer or distributor for instruction manual in local language(s).
- **German** : Bitte fragen Sie Ihren Händler nach eine Betriebsanleitung in Landessprache.
- **French** : S'il vous plait, veuillez demandez à votre fournisseur de manuel instruction en langue locale.
- **Spanish** : Por favor, contacte con su distribuidor para el manual de instrucciones en español.
- **Portuguese** : Por favor pessa ao seu agente ou distribuidor o manual de instruções em linguagem local.
- **Italian** : Per Manuale Istruzioni in lingua locale Vi preghiamo di rivolgervi al rivenditore o distributore.
- **Dutch** : Vraag uw handelaar om een nederlands-talige gebruiksaanwijzing.
- **Swedish** : Be er lokala Åtförsäljare eller distributör om manualer på svenska.
- **Danish** : Venligst henvend Dem til den danske distributør for instructions manualer.
- **Polish** : Prosze pyta swojego dealera lub dystrybutora o instrukcje obsługi w języku localnym.
- **中文** : 請向當地供應商或經銷商詢問中文使用說明書

## CONTENTS

	page
IMPORTANT SAFETY INSTRUCTIONS .....	2
GENERAL: TOOLS .....	2
GENERAL: PNEUMATIC TOOLS .....	3
INSTRUCTIONS FOR THIS TOOL .....	4
1. USAGE .....	4
2. CHECK THE CONTENTS OF THE PACKAGE .....	4
3. AIR SUPPLY .....	4
4. PREPARATION .....	5
5. HOW TO OPERATE THE TOOL .....	5
6. MAINTENANCE AND INSPECTION .....	6
7. THREAD SIZE OF HOSE FITTING .....	6
8. STORAGE .....	6
9. ORDERING SERVICE PARTS .....	6
10. OPTIONAL PARTS .....	6

## PICTOGRAM

-  Warning: It might be dangerous to operate the tool if the instructions supplied are not followed.
-  Using this tool improperly could result in serious injury. Read the instruction manual before use.
-  Always wear suitable eye protection.
-  Always wear suitable hearing protection.
-  Always wear respiratory protective equipment (PPE).
-  Always wear protective gloves for protection of hands from Vibration and Shock

The following Safety notations are used throughout the manual to highlight safety precautions for the user and for the tool.

 <b>WARNING:</b>	Indicates a potentially hazardous situation which, if not avoided by following the instructions given, could result in death or serious injury.
 <b>CAUTION:</b>	Indicates a potentially hazardous situation which, if not avoided by following the instructions given, could result in injury or material damage.

Please note, however, that failure to observe safety precautions under the “ Caution” category could result in a serious occurrence depending on the situation: please observe all safety precautions in the manual.

**Caution:** Important precautions for tool setup, operation and maintenance.

# IMPORTANT SAFETY INSTRUCTIONS

When using the tool, please observe the safety precautions below to prevent possible accident or injury.

## ⚠ Warning

Some dust created by power sanding, sawing, grinding, drilling, and other construction activities contains chemicals known [to the State of California] to cause cancer birth defects or other reproductive harm. Some examples of these chemicals are:

- lead from lead-based paints,
- crystalline silica from bricks and cement and other masonry products, and
- arsenic and chromium from chemically-treated lumber.

Your risk from these exposures varies, depending on how often you do this type of work. To reduce your exposure to these chemicals : work in a well ventilated area, and work with approved safety equipment, such as those dust masks that are specially designed to filter out microscopic particles.

## GENERAL: TOOLS

## ⚠ WARNING

### TO OPERATORS

#### • Wear proper clothing for the type of work being done.

Take care so that clothing, ties, hair, etc. will not become entangled with the moving parts. If items become entangled it will cause the operator to be pulled towards the tool and lead to possible cause of accident or injury.

#### • Always wear suitable eye protection.

Vision correction glasses are not safety glasses. Always wear appropriate safety glasses when doing your job.

#### • Always wear suitable hearing protection.

#### • Wear respiratory protective equipment (PPE).

Wear respiratory protective equipment (PPE) when working in an environment where dust particles are generated in operation.

#### • Always wear suitable protective gloves.

#### • Avoid working posture that is too stressful.

Always ensure a firm footing and well balanced posture.

#### • Do not operate the tool if you are too tired.

#### • Never touch any moving parts of the tool when running.

### ABOUT WORK AREA

#### • Keep the work area clean.

Cluttered work areas (e.g. workbench) invite accidents.

#### • Carefully select the work area.

Do not expose tool to rain.

Do not use tool in a wet or soaked area.

See that the work area is adequately illuminated.

#### • Never work near inflammable liquid or in a potentially explosive atmosphere.

#### • Keep children away from the work area.

Keep children and unauthorized people away from the work area to avoid accident or injury.

### BEFORE OPERATION

#### • Inspect tool before use.

Before using, check that screws are securely tightened, that any protective cover or guard is securely in place, other parts are free from damage and that the tool runs as it should.

Check that moving parts are properly adjusted for positioning and tightened, that parts are free from damage and properly mounted, and that all other parts are in good condition for normal operation.

Should you find any damage to the protective cover or other part, replace it in accordance with the Operation Manual. If there are no instructions in the Manual, please contact the sales agent through which you have purchased your tool or an authorized dealer near you for repair.

Likewise, if a switch failure occurs, contact sales agent through which you have purchased your tool or an authorized dealer near you for repair.

Do not use the tool if it does not start or stop with the start/stop switch.

#### • Securely mount cutter.

An improperly mounted cutter may fly out, causing possible damage to the tool or injury to the operator.

#### • Always remove spanner, wrench, etc., once adjustment has been made with them.

#### • Use a tool appropriate for the application.

Avoid heavy-duty application that is beyond the capacity of tool.

#### • Do not use the tool for purposes other than what it is designed for.

#### • Do not abuse tool.

Use tool in accordance with the specifications: you'll get the most out of it while ensuring safety.

#### • Securely fasten workpiece in place.

Use a vice or clamp to securely fasten the workpiece in place. It is much safer this way than holding it in your hand, allowing you to operate the tool with both hands.

## ABOUT HANDLING

- **How to store tool.**

When the tool is not used, store it in a dry area and out of reach of children.

- **How to carry tool.**

Do not touch the start switch while the tool is being carried.

- **Do not leave the tool unattended while it is running.**

Turn off the start switch and disconnect the tool from power source. Do not leave the work area until the tool comes to a complete stop.

## MAINTENANCE/SERVICE

- **Do not take apart or modify tool.**

Disassembly or modification carried out without the supervision of a qualified or authorized service engineer could result in an accident or injury.

- **Inspect cutting tool and accessories, etc.**

Always check to see that cutting tool and accessories, etc. are in good operating condition without damage or deterioration before you mount them on the tool. Should you find any damage to an accessory or part, please contact sales agent through which you have purchased your tool or an authorized dealer near you for repair.

- **Check parts for damage.**

When you have found damage to accessory or other part, carefully check the damaged part to determine the extent of influence it has upon the functions of the tool – that is, determine whether it can still perform its normal functions.

Check to see that the linkage of the moving parts is OK, that all parts are OK without damage, that they are properly mounted, and that the tool functions normally. Should you find any damage to an accessory or part that may hamper proper functioning of the tool, please contact sales agent through which you have purchased your tool or an authorized dealer near you for repair.

- **Have your tool repaired at an authorized Nitto Service Center.**

For repair or parts replacement, please contact the sales agent through which you have purchased your tool or an authorized dealer near you.

- **Use only Nitto genuine parts.**

Use of improper parts may result in serious accident. To obtain a Nitto genuine part, consult this Manual or contact the sales agent from which you have purchased your tool directly.

- **Do not detach label or nameplate from tool.**

When a label/nameplate gets damaged, worn or becomes missing, contact the sales agent through which you have purchased your tool or Nitto Kohki Co. Ltd, directly for a replacement.

## DISPOSAL

- When a tool is taken permanently out of service, it is advised that the tool is disassembled, degreased and parts separated by material and recycled locally in the appropriate manner.

# GENERAL:PNEUMATIC TOOLS

## ⚠ WARNING

- **Use appropriate air pressure.**

Excessively high air pressure will increase the tool number of revolutions or strokes causing not only potential premature failure/breakage but could also lead to an unexpected accident or injury.

- **Connect tool to air supply line.**

There are various types of pipes running in a factory in addition to the pneumatic line (such as oxygen, nitrogen, gas and water). For this reason, always ensure that you are connecting to the pneumatic line.

- **Start tool properly.**

Turn the start switch OFF before connecting to the air supply line.

- **Always disconnect the tool from the air supply line before putting on/taking off any accessory and prior to carrying out any maintenance work.**

- **Avoid exposure to exhaust air.**

Pneumatic tool exhaust air contains oil and contaminated moisture. Make sure the exhaust air is not directed towards your face or anyone else within the work area.

- **Keep tool off electricity.**

This pneumatic tool is not electrically insulated. To avoid a potential electric shock do not use where there is a possibility of coming into contact with live electricity.

## ⚠ CAUTION

- **Handle tool carefully.**

Abusive use of tool could invite failure or accident. Do not throw, drop or shock the tool.

- **Handle connecting hose carefully.**

Do not carry the tool by the connecting hose. Do not pull the connecting hose to disconnect.

# INSTRUCTIONS FOR THIS TOOL

## About Your Tool

### ⚠ WARNING

- **Wear protective glasses and a dustproof mask.**  
operation generates chips and dust particles, etc. which may cause eye and/or respiratory injury: Always use PPE (Personal Protective Equipment) for eye and respiratory protection.
- **Wear vibration reducing and shock absorbing gloves.**  
This is a power tool utilizing vibration. Wear vibration reducing and shock absorbing gloves. When your hands, fingers, arms, etc. feel discomfort during operations, immediately stop your work. Long hour operation should be prohibited, for it may cause Vibration - Induced disorder.
- **Always wear suitable hearing protection.**  
The tool generates loud noise. Always use ear plugs for hearing protection. Take necessary measures to comply with the local regulatory requirements and laws with regard to noise level, or do better.
- **Do not operate tool at no load.**  
Do not operate the tool at no load: It may not only cause damage to the tool but also may cause chisels to fracture and fly out, possibly resulting in unexpected accident.
- **Be sure to keep hands clear of chisel edge.**
- **Fix the chisel firmly. If the chisel is not fixed firmly , it may jump out and cause injury**

## 1. USAGE

This tool is for chipping work pieces with a chisel.

## 2. CHECK THE CONTENTS OF THE PACKAGE

Check the contents and make sure that the tool does not have any damage which may have occurred during transportation. The contents should correspond to the list as follows. In case of damage/missing parts, please contact the sales agent from whom you purchased the tool.

### ACH-16

Package Contents	Qty	Check
ACH-16	1	
Flat Chisel 20×120	1	
Bushing R3/8×NPT3/8	1	
Hose Nipple R3/8×3/8	1	
Instruction Manual	1	
Declaration of Conformity	1	
Caution for Use	1	

### CH-24

Package Contents	Qty	Check
CH-24	1	
Curved Flat Chisel 25×155	1	
Bushing R3/8×NPT3/8	1	
Hose Nipple R3/8×3/8	1	
Instruction Manual	1	
Declaration of Conformity	1	
Caution for Use	1	

## 3. AIR SUPPLY

### 3-1. Air Pressure

Adjust air pressure with the air regulator to the level appropriate for the pneumatic tool used.

Air pressure that is too low will fails the tool to operate at full capacity

Air pressure that is too high may cause damage to the tool.

### 3-2. Air Line (Fig.1)

Use a 9.5mm (3/8") I.D. connecting hose between the compressor and the tool.

Drained water, etc., if flown into the tool, could cause tool failure. Install an air filter, bsetween the compressor and the tool.




Fig. 1

### 3-3. Lubrication

Install an oiler between the compressor and the tool. Use the machine oil ISO VG-10. Failure to lubricate as required may result in damage to the tool. Use of oil that is too thick will reduce the performance of the tool.

### 3-4. Short hose fittings

Do not fix a coupling directly on the tool. Make sure that after a short hose is fixed with the Hose Nipple R3/8X3/8 including in the accessories, then the coupling be attached. If the couplings directly fixed, it would be damaged by the vibration and the life would be shortened.

## 4. PREPARATIONS

### ⚠ WARNING

**Turn off the air supply and disconnect the air supply hose before preparation for use.**

#### 4-1. Fixing the Attachment (Fig.2)

Fix the Hose Nipple to the Bushing (M16×Rc3/8) of the tool.




Fig.2

#### 4-2. Replacing Chisels

##### ACH-16 (Fig.3)

(1) For fixing the chisel, pull the Sleeve aligning the rectangular shaped groove on the chisel with the Throttle Lever (180°reversed side is also OK.) and push the chisel to the end and pull it slightly till the Sleeve returns to the External Retaining Ring. Then, if the Sleeve does not return, leave the hand off the Sleeve and turn the chisel left - and - right, or move it back and - forth. When the chisel comes to the set - position, the Sleeve automatically returns to the External Retaining Ring.

(2) For removing the chisel, pull the Sleeve and take out the chisel.




Fig.3

### CH-24 (Fig.4)

(1) Rotate the Stop Ring to align the hole in the Stop Ring with the Ball, the chisel can now be removed or mounted.

(2) To mount the chisel, align the relief groove on the shank with the Ball and insert the chisel until the Ball rests in the relief groove; twist the Stop Ring 180° to secure the chisel.




Fig.4


## 5. HOW TO OPERATE THE TOOL

### ⚠ WARNING

**Do not operate tool at no load.**

#### 5-1. Start and Stop (Fig.5)

(1) Before connecting to the air hose, make sure that the Throttle Lever is in OFF position.



(2) To start, hold the machine ON and press the Throttle Lever.

Fig.5

#### 5-2. Adjustment of Stroke (Fig.6) For ACH-16

Rotating the Adjust Valve (adjusting air flow) by a flat driver, the stroke can be adjusted. The maximum stroke can be obtained when the groove on the Valve align with the axis of the tool.




Fig.6

#### 5-3. Operating Procedure (Fig.7)

Grasp the Valve Body with one hand and place the chisel to the work piece. Hold the Cylinder with the other hand and press the Throttle Lever so that the chisel starts lightly hammering the work piece. Gradually press the lever harder to full operation after the cutting position has been determined; this will allow stable chipping work.




Fig.7

## 6. MAINTENANCE AND INSPECTION

When reshaping the edge of the chisel, apply water sometimes so that it may not be heated too much.

## 7. THREAD SIZE OF HOSE FITTING

The product comes with a metal-fitting with R thread. Connect the Bushing R thread X NPT thread included as standard accessories. If you would like to have American NPT thread instead.

## 8. STORAGE

### ⚠ CAUTION

**When tool is not used, store it out of reach of children.**

Avoid storing the tool in a location subject to high humidity, if the tool is left as it is used, residual moisture on the inside can cause rusting. Before storing, and after operation, oil the tool at the air inlet with machine oil ISO VG-10 and run it for a short time.

## 9. ORDERING SERVICE PARTS

For further operational and handling information or for replacement of parts and components, contact the company from whom you purchased the tool or an authorized dealer.

In ordering parts and components give each part number, part name and quantity required.

Use only NITTO genuine parts.

## 10. OPTIONAL PARTS

The following chisels are available from ex-stock.

### ACH-16




Fig.8

### CH-24




Fig.9